

XIAMEN GOODCOM TECHNOLOGY CO., LTD



Overview

Mobile thermal printer MTP58BN is a small, lightweight mobile receipt printer that brings user convenience and functionality to any mobile receipt printing application, such as: mobile POS / retail/ hospitality/ parking citations/ deliveries/ onboard transportation/ field repairs / installation / warehouse / logistics/ utility billing / meter reading.

Small and lightweight design, Long lasting rechargeable li-ion battery (3.7V, 2000 mAh), battery status indicator, smart battery management. Easy and convenient upgrades: customer oriented firmware.

Feature:

- Small and lightweight design
- Compatible with iOS, Android, Windows
- Easy and convenient upgrades
- UTF-8 encoded (multiple language supported)
- Long lasting li-ion battery
- Free SDK provided

Application:

- Mobile POS / retail
- Hospitality
- Parking citation
- Deliveries
- Onboard transportation
- Field repairs / installation
- Warehouse/Logistics
- Utility billing / tachograph

GOODCOM
Goodcom Technology CO.LTD

Model	MTP58BN	
Printing method	Direct thermo sensitive method	
Paper width	58 mm	
Valid printing width	48mm	
Weight (g)	185g	
Diameter of paper roller	45 mm	
Dot structure	384 dots /line	
Input character	ASCII CH(24×12),GB18240(24×24)	
Printing speed	40~60mm/s	
Lifetime	50km(printing density under 12.5%)/100 million pulses	
Printing content	English, figure, symbol, graph, barcode, Simplified / Traditional Chinese, Korean, Japanese, Arabic, Persian, French, German, Spanish, etc.	
Dot pitch (resolution)	203DPI/8 dots/mm	
Communication interface	USB	Bluetooth V4.0+ V3.0+V2.1
Power	3.7V, 2000mAh rechargeable li-ion battery	
Charging	USB charging or Standby charging / AC adapter	
Abnormal test	paper end /power capacity / cover switch	
Paper feeding	Easy paper loading	
Command sets	Compatible with ESC/POS command sets	
Paper cutter method	Manual	
Operation environment	Temperature -10°C~50°C ; Humidity 20%~85%	
Charging environment	Temperature 5°C~40°C; Humidity 20%~85%	
Storage environment	Temperature -20°C~70°C ; Humidity 5%~95%	
Standard accessories	Long-term preservable paper, AC adapter, li-ion battery	
Optional accessories	Serial cable / leather coat	